



www.minderresearch.com

3000 S.E. Waaler St.
Stuart, Florida 34997
772.463.6522

TireMinder TPMS Model TMG500HD Supplemental Instructions

To be used in conjunction with the TMG300C/TMG400C 14 page book.

Note:

- All setup, display and operating/warning functions of the Heavy Duty TMG500HD system are the same as outlined in the book for the model TMG400C.

Exceptions:

- **Page 7 item 10) "Transmitter Battery Replacement"**

The TMG500HD transmitters come with permanently installed US made batteries (Tadiran – Lithium Thionyl Chloride – Lead Free). These are manufactured to operate under the most extreme conditions (including Space). They will function for a minimum of 5 years.

When replacement is required, transmitters may be returned to Minder Research for proper recycling (plus a \$10.00 credit against new purchases).

- **Page 13 item 14) "Specifications"**

Sensor/Transmitter (TMT500HD)

Working Temperature -50°C to +85°C (-58°F to +185°F)

Dimension 28.5 X 27.5 X 27.5mm (1.12" X 1.08" X 1.08")

Weight 21 gm (0.74 oz)

Battery Tadiran Lithium Thionyl Chloride Cell (5 year non-replaceable).

Pressure Range 0-233 psi (TMT500HD)

All other Specifications are as printed in the original 14 page book.

